

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Pigment Carbon Black

Synonyms: Carbon Black, Pigment Carbon Black, Furnace Black, Channel Black

This MSDS is valid for following grades: Carbon Black grade series: FR910、FR960 、

FR940、FR890、FR970、FR8100、FR6800、FR5300、FR6600、FR6300、FR6700、FR6840、FR6406, FR6890, FR6860、FR6830、FR6890、FR8150 and so on.

Use of the Substance/Preparation: Various Industrial Products

Supplier: Shanghai FuRui Chemical Co., LTD

Address: Yigou New Type Manufacturing Industrial Park, Tangyin, Henan, China

Tel: 86-372-6227888

Fax: 86-372-6227888

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION: Black powder or pellets. Dust may be irritating to eyes and respiratory tract. Do not expose to temperatures above 300°C. Hazardous products of decomposition and/or combustion can include carbon monoxide, carbon dioxide, oxides of sulfur, and organic products of decomposition.

Principle Routes of Exposure: Inhalation, Eye contact, Skin contact.

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause mechanical irritation. Irritating, but will not permanently injure eye

tissue. Low hazard for usual industrial or commercial handling.

Skin Contact: No adverse effects expected.



SHANGHAI FURUI CHEMICAL CO., LTD

Inhalation: Dust may be irritating to respiratory tract. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. See also Section 8.

Ingestion: Health injuries are not known or expected under normal use. Low hazard for usual industrial or commercial handling.

Carcinogenic Effects: Substance listed by IARC (International Agency for Research on

Cancer). See also Section 11.

Target Organ Effects: Lungs

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorder

Potential Environmental Effects: No special environmental precautions required. Not

soluble in water. See also Section 12.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS Number EINECS Number Weight % EU Classification

Carbon Black 1333-86-4 215-609-9 100 None

4. FIRST AID MEASURES

Skin Contact: Wash thoroughly with soap and water. Seek medical attention if symptoms develop.

Eye Contact: Flush eyes immediately with large amounts of water for 15 minutes. Seek medical attention if symptoms develop.

Inhalation: If cough, shortness of breath or other breathing problems occur, move to fresh air. Seek medical attention if symptoms persist. If necessary, restore normal breathing through standard first aid measures.

Ingestion: Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.

Notes to Physician: Treat symptomatically.

5. FIRE AND IGNITION INFORMATION



SHANGHAI FURUI CHEMICAL CO., LTD

Extinguishing Media: Use foam, carbon dioxide (CO2), dry chemical or waterspray. A fog is recommended if water is used. DO NOT USE a solid water stream as it may scatter and spread fire.

Special Protective Equipment for Firefighters: Wear suitable protective equipment. In the event of fire, wear self-contained breathing apparatus.

Specific Hazards: It may not be obvious that carbon black is burning unless the material is stirred and sparks are apparent. Carbon black that has been on fire should be observed closely for at least hours to ensure no smoldering material is present. Burning produces irritant fumes. The product is insoluble and floats on water. If possible, try to contain floating material. This material creates a fire hazard because it floats on water.

Products: Carbon monoxide, Carbon dioxide, Oxides of sulphur, Organic products of decomposition.

Risk of Dust Explosion: Do not create a dust cloud by using a brush or compressed air.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: CAUTION: Wet carbon black produces slippery walking surfaces. Avoid dust formation. Ensure adequate ventilation. Use personal protective equipment. See also Section 8.

Methods for Cleaning Up: Clean up promptly by vacuum. Use of a vacuum with high efficiency particulate air (HEPA) filtration is recommended. Do not create a dust cloud by using a brush or compressed air. Pick up and transfer to properly labelled containers. See Section 13.

Environmental Precautions: Do not allow material to contaminate ground water system.

The product is insoluble and floats on water. If possible, try to contain floating material. Local authorities be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Do not breathe dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Do not create adust cloud by using a brush or compressed air. Fine dust is capable of penetrating electrical equipment and may cause electrical shorts. Take precautionary measures against static discharge.



SHANGHAI FURUI CHEMICAL CO., LTD

Storage: Keep in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Do not store together with strong oxidizing agents. Do not store together with volatile chemicals as they may be adsorbed onto product. Keep in properly labeled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS: The table below is a summary. Please see the specific legislation for complete information.

Carbon Black, CAS RN 1333-86-4: China: 4.0 mg/m₃, TWA

8.0 mg/m₃, STEL

Australia: 3.0 mg/m₃, TWA

Belgium - OEL: 3.6 mg/m₃, TWA

Canada: 3.5 mg/m₃, TWA

Finland: 3.5 mg/m₃, TWA

7.0 mg/m₃, STEL

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

ENGINEERING CONTROLS: Ensure adequate ventilation to maintain exposures below

occupational limits. Provide appropriate exhaust ventilation at

machinery and at places where dust can be generated.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: An approved air-purifying respirator (APR) for particulates may be

permissible where airborne concentrations are expected to exceed occupational exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air supplied respirator if there is any potential for uncontrolled release, exposure levels are not known, or any circumstances where air-purifying respirators may not provide adequate protection. Use of respirators must include a complete respiratory protection program in accordance with national

standards and current best practices.

Hand Protection: Wear protective gloves to prevent soiling of hands.

Eye Protection: Wear eye/face protection. Safety glasses with side-shields. Goggles.



SHANGHAI FURUI CHEMICAL CO., LTD

Skin and Body Protection: Wear suitable protective clothing. Wash clothing daily. Work clothing should not be allowed out of the workplace.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency eyewash and safety shower should be located nearby.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black Powder or Pellets

Odor: odorless

PH: 6-9(Furnace Black); 2-4(Channel Black)

Vapor Pressure: Not determined

Boiling Point/Range: Not applicable

Melting Point/Range: Not applicable

Water Solubility: Insoluble

Density: 1.7 - 1.9 g/cm3 @ 20°C

Bulk Density: 20 - 550 kg/m3

Specific Gravity: Not determined

% Volatile (by Weight): < 2.5% @ 950°C (non-oxidized carbon black)

2 - 11% (oxidized carbon black)

Evaporation Rate: Not applicable

Viscosity: Not determined

Partition Coefficient (n-octanol/water): Not determined

10. STABILITY AND REACTIVITY

Stability: Stable.

Reactivity: May react exothermically upon contact with strong oxidizers.

Incompatible Materials: Strong oxidizers such as chlorates, bromates, and nitrates.

Hazardous Polymerization: Hazardous polymerization does not occur.



SHANGHAI FURUI CHEMICAL CO., LTD

Mechanical Sensitivity (shock): Not sensitive to mechanical impact.

Conditions to Avoid: Do not expose to temperatures above 300°C. Keep away from

oxidizing agents in order to avoid exothermic reactions.

Hazardous Decomposition and/or

Combustion Products: Carbon monoxide, Carbon dioxide, Oxides of sulphur, Organic

products of decomposition.

Static Discharge Effects: Take precautionary measures against static discharges. Avoid

dust formation. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is

electrically earthed/grounded before beginning transfer

operations.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Oral LD50: LD50/oral/rat = > 8000 mg/kg.

Eye Irritation: Rabbit. Draize score 10-17/110 @ 24 hr. Non-irritating.

Skin Irritation: Rabbit. 0.6/8. Slight irritation.

SUBCHRONIC TOXICITY

Rat, inhalation, duration 90 days

NOAEL = 1.0 mg/m_3

Target organ: lungs

Effect: inflammation, hyperplasia, fibrosis.

CHRONIC TOXICITY

Rat, oral, duration: 2 years

Effect: no tumors

Mouse, oral, duration: 2 years

Effect: no tumors

Mouse, dermal, duration: 18 months



SHANGHAI FURUI CHEMICAL CO., LTD

Effect: no skin tumors

Rat, inhalation, duration: 2 years

Target organ: lungs

Effect: inflammation, fibrosis, tumors

Note: Tumors in the rat lung are related to the fine particle overload phenomenon rather than to a specific chemical effect of the dust particles in the lung. These effects in rats have been reported in studies on other inorganic insoluble particles and appear to be species specific. Tumors have not been observed in other species (i.e., mouse and hamster) for other insoluble particles under similar circumstances and study conditions.

Carcinogenic Effects: Substance listed by IARC (International Agency for Research Cancer). Does not contain any substances listed by NTP (National

Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental

Industrial Hygienists) or EU (European Union).

Carbon Black IARC Statement: There is inadequate evidence in humans for the

carcinogenicity of carbon black.

Reproductive Toxicity: Did not show effects in animal experiments.

Sensitizing Effects: Contains no known sensitizers.

Synergistic Materials: None reasonably foreseeable.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: Fish (Brachydanio rerio): LC50 (96hr) > 1,000 mg/L. (Method: OECD

203). Daphnia magna: EC50 (24hr) > 5,600 mg/L. (Method: OECD 202). Algae (Scenedesmus subspicatus): EC50 (72hr) > 10,000 mg/L. Algae (Scenedesmus subspicatus): NOEC >= 10,000 mg/L. Activated sludge:

EC0 (3hr) >= 800 mg/L. (Method: DEV L3 TTC test).

ENVIRONMENTAL FATE

Mobility: Not expected to migrate. Insoluble.

Bioaccumulation: Not expected due to physicochemical properties of the substance.

Persistence / Degradability: Not expected to degrade.

Distribution to Environmental Compartments: Insoluble. Expected to remain on soil

surface.



13. DISPOSAL CONSIDERATIONS

Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 2 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.

14. TRANSPORT INFORMATION

- Canadian Transport of Dangerous Goods Regulation
- European Transport of Dangerous Goods Regulation
- GGVS, GGVE, RID, ADR, IMDG Code, ICAO-TI
- United Nations (no UN number)
- US Department of Transportation

International Transportation

Identification: "Carbon black, non-activated, mineral origin". Not dangerous according to

IMDG-Code. Not dangerous according to ICAO-TI.

UN Number: None

UN Proper Shipping Name: Not classified

UN Shipping Class: Not classified

UN Packing Group: Not classified

US Rail Regulations: Not classified

REGULATORY INFORMATION **15**.

Hazard Classification

United States - OSHA (29 CFR 1910.1200): Hazardous.

Mexico - NOM-018-STPS-2000: Refer to HMIS Rating in Section 16.

Canada - WHMIS Classification (CPR, SOR/88-66): Class D2A.



This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and MSDS contains all the information required by the Controlled Products Regulations.

International Inventories

All components of this product are listed on or exempt from the following inventories:

- YES Australian Inventory of Chemical Substances (AICS)
- YES Canadian Domestic Substances List (DSL)
- YES Chinese Inventory
- YES European Inventory of Existing Commercial Chemical Substances (EINECS)
- YES Japanese Existing and New Chemical Substances (ENCS)
- YES Korean Existing Chemicals List (KECL)
- YES New Zealand Hazardous Substances and New Organisms Act (HSNO)
- YES Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- YES United States Toxic Substances Control Act (TSCA) Inventory

16. OTHER INFORMATION

Carbon Black Extracts: Manufactured carbon blacks generally contain less than 0.1% of solvent extractable polycyclic aromatic hydrocarbons (PAH).

Solvent extractable PAH content depends on numerous factors including, but not limited to, the manufacturing process, desired product specifications, and the analytical procedure used to measure and identify solvent extractable materials.

General Information: The carbon black industry continues to sponsor research designed to identify adverse health effects from long term exposure to carbon black. This MSDS will be updated as new safety and health information may become available.

Supplier: Shanghai FuRui Chemical Co., LTD

Address: Yigou New Type Manufacturing Industrial Park, Tangyin, Henan, China.



上海复瑞化工有限公司 SHANGHAI FURUI CHEMICAL CO., LTD

Tel: 86-372-6227888

Fax: 86-372-6227888

Website: http://www.shfrhg.com

http://www.tyfrth.com

The information set force is based on information that Shanghai FuRui Chemical Co., LTD believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Shanghai FuRui Chemical Co., LTD assumes no legal responsibility for use or reliance thereon.