

Chemical Safety Data Sheet MSDS / SDS

5-Methyl-2-hexanone

Revision Date:2024-03-16 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : 5-Methyl-2-hexanone
CBnumber : CB7397123
CAS : 110-12-3
EINECS Number : 203-737-8
Synonyms : 5-methyl-2-hexanone,5-methylhexan-2-one

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification**Classification of the substance or mixture**

Flammable liquids, Category 3
Acute toxicity - Category 4, Inhalation

Label elements**Pictogram(s)**

☐

Signal word : Warning

Hazard statement(s)

H226 Flammable liquid and vapour
H332 Harmful if inhaled

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

P370+P378 In case of fire: Use ... to extinguish.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P317 Get medical help.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards

no data available

SECTION 3: Composition/information on ingredients

Substance

Product name	: 5-Methyl-2-hexanone
Synonyms	: 5-methyl-2-hexanone,5-methylhexan-2-one
CAS	: 110-12-3
EC number	: 203-737-8
MF	: C7H14O
MW	: 114.19

SECTION 4: First aid measures

Description of first aid measures

If inhaled

Fresh air, rest. Refer for medical attention.

Following skin contact

First rinse with plenty of water for at least 15 minutes, then remove contaminated clothes and rinse again. Refer for medical attention .

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth. Do NOT induce vomiting. Refer for medical attention .

Most important symptoms and effects, both acute and delayed

Excerpt from ERG Guide 127 [Flammable Liquids (Water-Miscible)]: Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. (ERG, 2016)

Indication of any immediate medical attention and special treatment needed

INHALATION. Symptoms: Cough. Headache. Dizziness. Drowsiness. Labored breathing. Sore throat. First aid: Fresh air, rest. Refer for medical attention. SKIN: Symptoms: Dry skin. Redness. First aid: First rinse with plenty of water, then remove contaminated clothes and rinse again. Refer for medical attention. EYES: Symptoms: Redness. First aid: First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor. INGESTION: Symptoms: Nausea. First aid: Rinse mouth. Do NOT induce vomiting. Refer for medical attention.

SECTION 5: Firefighting measures

Extinguishing media

If material on fire or involved in fire: Do not extinguish fire unless flow can be stopped or safely confined. Use water in flooding quantities as fog. Solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water. Apply water from as far a distance as possible. Use alcohol foam, dry chemical or carbon dioxide. Keep run-off water out of sewers and water sources.


Specific Hazards Arising from the Chemical

Excerpt from ERG Guide 127 [Flammable Liquids (Water-Miscible)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. (ERG, 2016)

Advice for firefighters

Use AFFF, alcohol-resistant foam, powder, carbon dioxide. In case of fire: keep drums, etc., cool by spraying with water.

NFPA 704



■ HEALTH 1 Exposure would cause irritation with only minor residual injury (e.g. [acetone](#), sodium bromate, potassium chloride)

Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature

FIRE 3 conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

SPEC.

HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Ventilation. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations. Do NOT wash away into sewer.

Environmental precautions

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Ventilation. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations. Do NOT wash away into sewer.

Methods and materials for containment and cleaning up

Evacuate and restrict persons not wearing protective equipment from area of spill or leak until cleanup is complete. Remove all ignition sources. Establish forced ventilation to keep levels below explosive limit. Absorb liquids in vermiculite, dry sand, earth, peat, carbon, or similar material and deposit in sealed containers. Keep this chemical out of a confined space ... because of the possibility of an explosion ... It may be necessary to contain and dispose of this chemical as a hazardous waste. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Contact your Department of Environmental Protection or your regional office of the federal EPA for specific recommendations. If employees are required to clean up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

SECTION 7: Handling and storage

Precautions for safe handling

NO open flames, NO sparks and NO smoking. Above 36°C use a closed system, ventilation and explosion-proof electrical equipment. Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

Conditions for safe storage, including any incompatibilities

Fireproof.... Store in tightly closed containers in a cool, well ventilated area away from sources of oxidizers (such as perchlorates, peroxides, permanganates, chlorates, and nitrates), strong oxidizers (such as chlorine, bromine, and fluorine), reducing agents, and aldehydes. Sources of ignition such as smoking and open flames are prohibited where methyl isoamyl ketone is handled, used or stored. Metal containers involving the transfer of 5 gallons or more of methyl isoamyl ketone should be grounded and bonded. Drums must be equipped with self-closing valves, pressure vacuum bungs, and flame arresters.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational Exposure limit values

TLV: 20 ppm as TWA; 50 ppm as STEL.MAK: 47 mg/m³, 10 ppm; peak limitation category: I(2); pregnancy risk group: D.EU-OEL: 95 mg/m³, 20 ppm as TWA

Biological limit values

no data available

Exposure controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

Individual protection measures

Eye/face protection

Wear safety spectacles or eye protection in combination with breathing protection.

Skin protection

Protective gloves. Protective clothing.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Physical state	Liquid
Colour	Clear colorless
Odour	Pleasant, fruity odor
Melting point/freezing point	-73.9 °C. Atm. press.:1 atm.
Boiling point or initial boiling point and boiling range	144 °C. Atm. press.:1 atm.
Flammability	Class IC Flammable Liquid: Fl.P. at or above 73°F and below 100°F.
Lower and upper explosion limit/flammability limit	1.35-8.2%, 93°F
Flash point	36 °C. Atm. press.:101.325 kPa.
Auto-ignition temperature	400 °C. Atm. press.:1 atm.
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	dynamic viscosity (in mPa s) = 0.704. Temperature:25.0°C.
Solubility	water: soluble5.4g/L at 25°C
Partition coefficient n-octanol/water	log Pow = 1.94. Temperature:25 °C.

Vapour pressure	4.5 mm Hg (20 °C)
Density and/or relative density	0.81 g/cm ³ . Temperature:20 °C.
Relative vapour density	3.94 (vs air)
Particle characteristics	no data available

SECTION 10: Stability and reactivity

Reactivity

Reacts violently with strong oxidants, strong bases, amines and isocyanates. This generates fire and explosion hazard. Attacks some plastics.

Chemical stability

Stable containers: drums; tank cars

Possibility of hazardous reactions

FlammableThe vapour mixes well with air, explosive mixtures are easily formed. Ketones, such as 5-METHYLHEXAN-2-ONE, are reactive with many acids and bases liberating heat and flammable gases (e.g., H₂). The amount of heat may be sufficient to start a fire in the unreacted portion of the ketone. Ketones react with reducing agents such as hydrides, alkali metals, and nitrides to produce flammable gas (H₂) and heat. Ketones are incompatible with isocyanates, aldehydes, cyanides, peroxides, and anhydrides. They react violently with aldehydes, HNO₃, HNO₃ + H₂O₂, and HClO₄.

Conditions to avoid

no data available

Incompatible materials

The vapor mixes well with air, explosive mixtures are easily formed.

Hazardous decomposition products

When heated to decomposition it emits acrid smoke and irritating fumes.

SECTION 11: Toxicological information

Acute toxicity

- Oral: LD₅₀ - rat (male) - 5 657 mg/kg bw. Remarks:The two highest dose levels (4000 and 8000 mg/kg bw) used in this study were higher than that used for a limit dose in present-day guideline studies.
- Inhalation: LC₅₀ - rat (male) - > 3 207 - < 5 875 ppm.
- Dermal: LDLo - guinea pig - > 10 mL/kg bw.

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

The substance is irritating to the eyes, skin and respiratory tract. The substance may cause effects on the kidneys. This may result in kidney impairment. Exposure above the OEL could cause lowering of consciousness.

STOT-repeated exposure

Repeated or prolonged contact with skin may cause dermatitis.

Aspiration hazard

A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C; rather slowly.

SECTION 12: Ecological information

Toxicity

Toxicity to fish: LC50 - Pimephales promelas - 159 mg/L - 96 h.

Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna - > 100 mg/L - 48 h.

Toxicity to algae: EC50 - Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) - > 100 mg/L - 72 h.

Toxicity to microorganisms: EC50 - activated sludge of a predominantly domestic sewage - > 1 000 mg/L - 3 h. Remarks:Respiration rate.

Persistence and degradability

no data available

Bioaccumulative potential

An estimated BCF of 6 was calculated in fish for 5-methyl-2-hexanone(SRC), using a log Kow of 1.88(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

Mobility in soil

The Koc of 5-methyl-2-hexanone is estimated as 250(SRC), using a log Kow of 1.88(1) and a regression-derived equation(2). According to a classification scheme(3), this estimated Koc value suggests that 5-methyl-2-hexanone is expected to have moderate mobility in soil.

Other adverse effects

no data available

SECTION 13: Disposal considerations

Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

UN Number

ADR/RID: UN2302 (For reference only, please check.)

IMDG: UN2302 (For reference only, please check.)

IATA: UN2302 (For reference only, please check.)

UN Proper Shipping Name

ADR/RID: 5-METHYLHEXAN-2-ONE (For reference only, please check.)

IMDG: 5-METHYLHEXAN-2-ONE (For reference only, please check.)

IATA: 5-METHYLHEXAN-2-ONE (For reference only, please check.)

Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

Special precautions for user

no data available

Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

EC Inventory

Listed.

United States Toxic Substances Control Act (TSCA) Inventory

Listed.

China Catalog of Hazardous chemicals 2015

Listed.

New Zealand Inventory of Chemicals (NZIoC)

Listed.

PICCS

Listed.

Vietnam National Chemical Inventory

Listed.

IECSC

Listed.

Korea Existing Chemicals List (KECL)

Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.