Chemical Safety Data Sheet MSDS / SDS

Benzyl chloroformate

Revision Date: 2023-12-07 Revision Number: 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Benzyl chloroformate

 CBnumber
 : CB7853678

 CAS
 : 501-53-1

 EINECS Number
 : 207-925-0

Synonyms : Cbz,benzyl chloroformate

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.

Uses advised against : none

Company Identification

Company : Chemicalbook

Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word Danger

Precautionary statements

P501 Dispose of contents/container to.....

P406 Store in corrosive resistant/... container with a resistant inner liner.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P391 Collect spillage. Hazardous to the aquatic environment

P390 Absorb spillage to prevent material damage.

P370+P378 In case of fire: Use \dots for extinction.

P310 Immediately call a POISON CENTER or doctor/physician.

P309 IF exposed or if you feel unwell:

P307+P311 IF exposed: call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P284 Wear respiratory protection.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P270 Do not eat, drink or smoke when using this product.

P264 Wash skin thouroughly after handling.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P240 Ground/bond container and receiving equipment.

P234 Keep only in original container.

P233 Keep container tightly closed.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P202 Do not handle until all safety precautions have been read and understood.

P201 Obtain special instructions before use.

Hazard statements

H410 Very toxic to aquatic life with long lasting effects

H401 Toxic to aquatic life

H400 Very toxic to aquatic life

H372 Causes damage to organs through prolonged or repeated exposure

H370 Causes damage to organs

H360 May damage fertility or the unborn child

H350 May cause cancer

H336 May cause drowsiness or dizziness

H335 May cause respiratory irritation

H332 Harmful if inhaled

H330 Fatal if inhaled

H318 Causes serious eye damage

H314 Causes severe skin burns and eye damage

H304 May be fatal if swallowed and enters airways

H303 May be harmfulif swallowed

H290 May be corrosive to metals

H227 Combustible liquid

H225 Highly Flammable liquid and vapour

SECTION 3: Composition/information on ingredients

Substance

Product name : Benzyl chloroformate

Synonyms : Cbz,benzyl chloroformate

CAS : 501-53-1

EC number : 207-925-0
MF : C8H7ClO2
MW : 170.59

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Hydrogen chloride gas Phosgene

Carbon oxides Hydrogen chloride gas Combustible.

Vapors are heavier than air and may spread along floors. Risk of dust explosion.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

Advice for firefighters


Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable

protective clothing.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquidabsorbent material (e.g.

Chemizorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stability

Recommended storage temperature

-20 °C

Moisture sensitive. Heat sensitive. Over time, pressure may increase causing containers to burst

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Full contact

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Material: Fluorinated rubber Minimum layer thickness: 0,7 mm

Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	light yellow liquid, clear
Odour	pungent
Odour Threshold	No data available
рН	No data available
Melting point/freezing point	Melting point/range: -18 °C
Initial boiling point and boiling range	152 °C
Flash point	92 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive	No data available
limits	
Vapour pressure	95,809 hPa at 20 °C 195,065 hPa at 55 °C
Vapour density	5,89 - (Air = 1.0)
Relative density	1,217 g/cm3 at 20 °C No data available
Water solubility	Miscible with ether, acetone and benzene.
Partition coefficient: n-octanol/water	No data available

Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

Relative vapor density

5,89 - (Air = 1.0)

SECTION 10: Stability and reactivity

Reactivity

Can violently decompose at elevated temperatures Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical. Contact with water liberates toxic gas.

Chemical stability

To avoid thermal decomposition, do not overheat. Decomposes when moist.

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

May decompose on exposure to moist air or water.

Conditions to avoid

Heat, flames and sparks. Exposure to moisture. Do not heat over: 75° C Strong heating.

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - > 2.000 mg/kg (Calculation method)

Inhalation

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Toxicity

LD50 orally in Rabbit: 3000 mg/kg

SECTION 12: Ecological information

Toxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

SECTION 14: Transport information

UN number

ADR/RID: 1739 IMDG: 1739 IATA: 1739

UN proper shipping name

ADR/RID: BENZYL CHLOROFORMATE IMDG: BENZYL CHLOROFORMATE

IATA: Benzyl chloroformate

Passenger Aircraft: Not permitted for transport

Transport hazard class(es)

ADR/RID: 8 IMDG: 8

Packaging group 14.4

ADR/RID: I IMDG: I IATA: I

Environmental hazards 14.5

ADR/RID: yes IMDG Marine pollutant: yes IATA: no

Special precautions for user 14.6

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

Measures for Environmental Management of New Chemical Substances

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/

Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/

EC Inventory:Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

SECTION 16: Other information

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit
TWA: Time Weighted Average

References

[1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple

[2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp

[3] ECHA - European Chemicals Agency, website: https://echa.europa.eu/

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0®uest_locale=en

[5] ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg

[6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp

[7] HSDB - Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm

[8] IARC - International Agency for Research on Cancer, website: http://www.iarc.fr/

[9] IPCS - The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home

[10] Sigma-Aldrich, website: https://www.sigmaaldrich.com/

Other Information

The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort.Rest and medical observation is therefore essential.Immediate administration of an appropriate inhalation therapy by a doctor or a person authorized by him/her, should be considered.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.