

## Chemical Safety Data Sheet MSDS / SDS

**Butylated Hydroxytoluene**

Revision Date:2024-04-20 Revision Number:1

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product identifier**

Product name : Butylated Hydroxytoluene  
CBnumber : CB8355755  
CAS : 128-37-0  
EINECS Number : 204-881-4  
Synonyms : BHT,Butylated Hydroxytoluene

**Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.  
Uses advised against : none

**Company Identification**

Company : Chemicalbook  
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing  
Telephone : 400-158-6606

**SECTION 2: Hazards identification****GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Warning

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continuerinsing.  
P307+P311 IF exposed: call a POISON CENTER or doctor/physician.

P391 Collect spillage. Hazardous to the aquatic environment

P405 Store locked up.

P501 Dispose of contents/container to.....

#### **Hazard statements**

H302 Harmful if swallowed

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H370 Causes damage to organs

H373 May cause damage to organs through prolonged or repeated exposure

H401 Toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long lasting effects

---

## SECTION 3: Composition/information on ingredients

### **Substance**

|              |                                     |
|--------------|-------------------------------------|
| Product name | : Butylated Hydroxytoluene          |
| Synonyms     | : BHT, Butylated Hydroxytoluene     |
| CAS          | : 128-37-0                          |
| EC number    | : 204-881-4                         |
| MF           | : C <sub>15</sub> H <sub>24</sub> O |
| MW           | : 220.35                            |

---

## SECTION 4: First aid measures

### **Description of first aid measures**

#### **If inhaled**

After inhalation: fresh air.

#### **In case of skin contact**

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### **In case of eye contact**

After eye contact: rinse out with plenty of water. Remove contact lenses.

#### **If swallowed**

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

### **Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### **Indication of any immediate medical attention and special treatment needed**

No data available

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### Special hazards arising from the substance or mixture

Carbon oxides Combustible.

Vapors are heavier than air and may spread along floors. Risk of dust explosion.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.


### Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

### NFPA 704



**HEALTH 0** Poses no health hazard, no precautions necessary and would offer no hazard beyond that of ordinary combustible materials

**FIRE 1** Materials that require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. Includes some finely divided suspended solids that do not require heating before ignition can occur. Flash point at or above 93.3 °C (200 °F). (e.g. [mineral oil](#), ammonia)

**REACT 0** Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N<sub>2</sub>](#))

**SPEC.**

**HAZ.**

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

### **Environmental precautions**

Do not let product enter drains.

### **Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

### **Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **Precautions for safe handling**

For precautions see section 2.2.

### **Conditions for safe storage, including any incompatibilities**

### **Storage conditions**

Tightly closed. Dry. Tightly closed. Dry.

### **Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **control parameter**

### **Hazard composition and occupational exposure limits**

Does not contain substances with occupational exposure limits.

### **Exposure controls**

### **Personal protective equipment**

#### **Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### **Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

### Respiratory protection

Recommended Filter type: Filter A-(P2)

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

### Control of environmental exposure

Do not let product enter drains.

---

## SECTION 9: Physical and chemical properties

### Information on basic physicochemical properties

|  |   |
|--|---|
| Appearance                                   | colorless powder, crystalline   |
| Odour  | odorless  |
| Odour Threshold                              | Not applicable  |
| pH   | No data available   |
| Melting point/freezing point                 | Melting point/range: 69 - 73 °C - lit.  |
| Initial boiling point and boiling range      | 265 °C - lit.   |
| Flash point                                  | 127 °C - open cup   |
| Evaporation rate                             | No data available   |
| Flammability (solid, gas)                    | No data available   |
| Upper/lower flammability or explosive limits | No data available   |
| Vapour pressure                              | 0,00 hPa at 25 °C - OECD Test Guideline 104                                   |
| Vapour density                               | 7.6 (vs air)  |
| Relative density                             | No data available   |
| Water solubility                             | 0,76 g/l at 20 °C - OECD Test Guideline 105- slightly soluble                 |
| Partition coefficient: n-octanol/water       | log Pow: 5,1 - - Potential bioaccumulation                                    |
| Autoignition temperature                     | >400 °C - Regulation (EC) No. 440/2008, Annex, A.16                           |
| Decomposition temperature                    | No data available   |
| Viscosity                                    | Viscosity, kinematic: No data available Viscosity, dynamic: No data available |
| Explosive properties                         | No data available   |
| Oxidizing properties                         | No data available   |

### Other safety information

No data available

## SECTION 10: Stability and reactivity

### Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

### Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) . The product is chemically stable under standard ambient conditions (room temperature) .

### Possibility of hazardous reactions

Violent reactions possible with:

Peroxides bases sulfuric acid Strong acids

Acid chlorides Acid anhydrides Oxidizing agents Bases

### Conditions to avoid

Strong heating. Strong heating.

### Incompatible materials

Copper, copper compounds, brass, Mild steel

### Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - > 6.000 mg/kg

(OECD Test Guideline 401) Inhalation

LD50 Dermal - Rat - male and female - > 2.000 mg/kg (OECD Test Guideline 402)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

#### **Respiratory or skin sensitization**

Patch test: - In vitro study

Result: negative Remarks: (ECHA)

#### **Germ cell mutagenicity**

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Result: negative

Remarks: (ECHA)

Test Type: In vitro mammalian cell gene mutation test Test system: rat hepatocytes

Metabolic activation: Metabolic activation Result: negative

Remarks: (ECHA)

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation Result: negative

Remarks: (ECHA)

Test Type: Micronucleus test Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Result: negative Remarks: (ECHA)

Test Type: Chromosome aberration test Species: Rat

Cell type: Bone marrow Application Route: Oral

Result: negative Remarks: (ECHA)

#### **Carcinogenicity**

No data available

#### **Reproductive toxicity**

No data available

#### **Specific target organ toxicity - single exposure**

No data available

#### **Specific target organ toxicity - repeated exposure**

No data available

#### **Aspiration hazard**

No data available

#### **Toxicity**

LD50 orally in mice: 1040 mg/kg (McOmie)

---

## SECTION 12: Ecological information

### **Toxicity**

#### **Toxicity to fish**

semi-static test LC50 - Danio rerio (zebra fish) - > 0,57 mg/l - 96 h (Directive 67/548/EEC, Annex V, C.1.)

#### **Toxicity to daphnia and other aquatic invertebrates**

static test EC50 - Daphnia magna (Water flea) - 0,48 mg/l - 48 h (OECD Test Guideline 202)

#### **Toxicity to algae**

static test ErC50 - *Desmodesmus subspicatus* (green algae) - > 0,4 mg/l - 72 h

(Directive 67/548/EEC, Annex V, C.3.)

static test EC10 - *Desmodesmus subspicatus* (green algae) - ca. 0,4 mg/l - 72 h

(Directive 67/548/EEC, Annex V, C.3.)

#### **Toxicity to bacteria**

static test EC50 - activated sludge - > 10.000 mg/l - 3 h (OECD Test Guideline 209)

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **Other adverse effects**

No data available

---

## SECTION 13: Disposal considerations

### **Waste treatment methods**

#### **Incompatibilities**

Butylated hydroxytoluene is incompatible with strong oxidizing agents such as peroxides and permanganates. Contact with oxidizing agents may cause spontaneous combustion. Iron salts cause discoloration with loss of activity. Heating with catalytic amounts of acids causes rapid decomposition with the release of the flammable gas isobutene.

#### **Product**

See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

### **UN number**

ADR/RID: 3077 IMDG: 3077 IATA: 3077

### **UN proper shipping name**

ADR/RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (butyl hydroxytoluene (BHT))

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (butyl



hydroxytoluene (BHT))

IATA: Environmentally hazardous substance, solid, n.o.s. (butyl hydroxytoluene (BHT))

### **Transport hazard class(es)**

ADR/RID: 9 IMDG: 9 IATA: 9

### **Packaging group**

ADR/RID: III IMDG: III IATA: III

### **Environmental hazards**

ADR/RID: yes IMDG Marine pollutant: yes IATA: yes

### **Special precautions for user**

### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids. Packages smaller than or equal to 5 kg / L , not dangerous goods of Class 9

---

## SECTION 15: Regulatory information

### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Regulations on the Safety Management of Hazardous Chemicals**

China Catalog of Hazardous chemicals 2015:Not Listed. website: <https://www.mem.gov.cn/>

#### **Measures for Environmental Management of New Chemical Substances**

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

EC Inventory:Listed.

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

---

## SECTION 16: Other information

### **Abbreviations and acronyms**

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

## References

- 【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- 【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- 【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>
- 【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:  
[http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)
- 【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- 【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- 【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- 【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- 【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- 【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

### Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.