Chemical Safety Data Sheet MSDS / SDS

Chlorodimethylsilane

Revision Date: 2025-02-01 Revision Number: 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Chlorodimethylsilane

CBnumber : CB3694606

CAS : 1066-35-9

EINECS Number : 213-912-0

Synonyms : chlorodimethylsilane,DMCS

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.

Uses advised against : none

Company Identification

Company : Chemicalbook

Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word Danger

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P231+P232 Handle under inert gas. Protect from moisture.

P233 Keep container tightly closed.

P234 Keep only in original container.

P240 Ground/bond container and receiving equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P264 Wash skin thouroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P370+P378 In case of fire: Use ... for extinction.

P390 Absorb spillage to prevent material damage.

P403 Store in a well-ventilated place.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P406 Store in corrosive resistant/... container with a resistant inner liner.

P501 Dispose of contents/container to.....

Hazard statements

H224 Extremely flammable liquid and vapour

H225 Highly Flammable liquid and vapour

H261 In contact with water releases flammable gas

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H331 Toxic if inhaled

SECTION 3: Composition/information on ingredients

Substance

Product name : Chlorodimethylsilane

Synonyms : chlorodimethylsilane,DMCS

CAS : 1066-35-9

EC number : 213-912-0

MF : C2H7CISi

MW : 94.62

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

Foam Water

Special hazards arising from the substance or mixture

Carbon oxides Hydrogen chloride gas silicon oxides Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors. May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



Short exposure could cause serious temporary or moderate residual injury (e.g. <u>liquid hydrogen, sulfuric acid, calcium hypochlorite</u>, hexafluorosilicic acid)

Will rapidly or completely vaporize at normal atmospheric pressure and temperature, or is readily dispersed in air and will

FIRE 4 burn readily. Includes pyrophoric substances. Flash point below room temperature at 22.8 °C (73 °F). (e.g. acetylene, propane, <u>hydrogen gas</u>)

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, N2)

	SPEC.	M			
Ш	HAZ.	VV			

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquidabsorbent material (e.g.

Chemizorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Keep workplace dry. Do not allow product to come into contact with water.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons. Never allow product to get in contact with water during storage.

Storage stability

Recommended storage temperature 2 - 8 °C

Handle and store under inert gas. Moisture sensitive.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton?

Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested:Vitoject? (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 30 min Material tested:Camatril? (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	colorless clear, liquid			
Odour	No data available			
Odour Threshold	No data available			
рН	No data available			
Melting point/freezing point	Melting point/range: -111 °C - lit.			
Initial boiling point and boiling range	34,7 °C - lit.			
Flash point	-23 °C - closed cup			
Evaporation rate	No data available			
Flammability (solid, gas)	No data available			
Upper/lower flammability or explosive	Upper explosion limit: 20 %(V) Lower explosion limit: 3 %(V)			
limits				
Vapour pressure	590,19 hPa at 20 °C 1.924,5 hPa at 55 °C			
Vapour density	3,27 - (Air = 1.0)			
Relative density	0.868			
Water solubility	Miscible with organic solvents.			
Partition coefficient: n-octanol/water	No data available			
Autoignition temperature	250 °C at 1013,0 hPa			
Decomposition temperature	No data available			
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available			
Explosive properties	No data available			
Oxidizing properties	No data available			

Other safety information

Relative vapor density

3,27 - (Air = 1.0)

SECTION 10: Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

Chemical stability

sensitive to moisture

Possibility of hazardous reactions

Violent reactions possible with:

Water Alcohols Amines alkalines acids

Conditions to avoid

Warming. Moisture.

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LC50 Inhalation - Rat - male and female - 1 h - 8,66 mg/l (OECD Test Guideline 403)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The initial threshold screening levels (ITSLs) for chlorodimethylsilane (CDMS) are 5400 μ g/m3 (1-hr averaging time) and 52 μ g/m3 (annual averaging time).

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

UN number

ADR/RID: 2988 IMDG: 2988 IATA: 2988

UN proper shipping name

 $ADR/RID: CHLOROSILANES, WATER-REACTIVE, FLAMMABLE, CORROSIVE, N.O.S.\ IMDG: CHLOROSILANES, WATER-REACTIVE, FLAMMABLE, CORROSIVE, WATER-REACTIVE, FLAMMABLE, CORROSIVE, WATER-REACTIVE, WATER-REACTIVE, FLAMMABLE, CORROSIVE, WATER-REACTIVE, WATER-REA$

FLAMMABLE, CORROSIVE, N.O.S.

IATA: Chlorosilanes, water-reactive, flammable, corrosive, n.o.s. Passenger Aircraft: Not permitted for transport

Transport hazard class(es)

ADR/RID: 4.3 (3, 8) IMDG: 4.3 (3, 8) IATA: 4.3 (3)(8)

Packaging group

ADR/RID: I IMDG: I IATA: I

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Not Listed. website: https://www.mem.gov.cn/

Measures for Environmental Management of New Chemical Substances

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/

New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

EC Inventory:Listed.

Korea Existing Chemicals List (KECL):Not Listed. website: http://ncis.nier.go.kr

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

- [1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple
- [2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp
- [3] ECHA European Chemicals Agency, website: https://echa.europa.eu/
- [4] eChemPortal The Global Portal to Information on Chemical Substances by OECD, website:

 $http://www.echemportal.org/echemportal/index?pageID=0\&request_locale=en$

- [5] ERG Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg
- [6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp
- [7] HSDB Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm
- [8] IARC International Agency for Research on Cancer, website: http://www.iarc.fr/
- [9] IPCS The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home

【10】 Sigma-Aldrich, website: https://www.sigmaaldrich.com/

Disclaimer

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.