

## Chemical Safety Data Sheet MSDS / SDS

## Isobutyl acrylate

Revision Date:2023-12-30 Revision Number:1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier**

Product name : Isobutyl acrylate  
CBnumber : CB8382708  
CAS : 106-63-8  
EINECS Number : 203-417-8  
Synonyms : IBA,Isobutyl acrylate

**Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.  
Uses advised against : none

**Company Identification**

Company : Chemicalbook  
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing  
Telephone : 400-158-6606

## SECTION 2: Hazards identification

**Classification of the substance or mixture**

Flammable liquids, Category 3  
Acute toxicity - Category 4, Dermal  
Skin irritation, Category 2  
Skin sensitization, Category 1  
Acute toxicity - Category 4, Inhalation

**Label elements****Pictogram(s)**

☐☐☐

Signal word : Warning

**Hazard statement(s)**

H226 Flammable liquid and vapour  
H311 Toxic in contact with skin  
H312 Harmful in contact with skin  
H315 Causes skin irritation

H317 May cause an allergic skin reaction

H320 Causes eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation

H412 Harmful to aquatic life with long lasting effects

#### **Precautionary statement(s)**

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use ... for extinction.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to.....

#### **Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P264 Wash ... thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

#### **Response**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

P370+P378 In case of fire: Use ... to extinguish.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P317 Get medical help.

P321 Specific treatment (see ... on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P317 If skin irritation occurs: Get medical help.

P333+P317 If skin irritation or rash occurs: Get medical help.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

#### **Disposal**

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

#### **Other hazards**

no data available

---

## SECTION 3: Composition/information on ingredients

### **Substance**

Product name	: Isobutyl acrylate
Synonyms	: IBA, Isobutyl acrylate
CAS	: 106-63-8
EC number	: 203-417-8
MF	: C <sub>7</sub> H <sub>12</sub> O <sub>2</sub>
MW	: 128.17

---

## SECTION 4: First aid measures

### **Description of first aid measures**

#### **If inhaled**

Move the victim into fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and consult a doctor immediately.

Do not use mouth to mouth resuscitation if the victim ingested or inhaled the chemical.

#### **Following skin contact**

Take off contaminated clothing immediately. Wash off with soap and plenty of water. Consult a doctor.

#### **Following eye contact**

Rinse with pure water for at least 15 minutes. Consult a doctor.

#### **Following ingestion**

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

### **Most important symptoms and effects, both acute and delayed**

Moderate toxicity when swallowed. Contact with the eyes causes minor irritation no worse than that caused by hand soap. (USCG, 1999)

### **Indication of any immediate medical attention and special treatment needed**

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature.

## SECTION 5: Firefighting measures

### Extinguishing media

This chemical is a combustible liquid. Poisonous gases are produced in fire. Use dry chemical, carbon dioxide, or foam extinguishers. Water may be ineffective. Vapors are heavier than air and will collect in low areas. Vapors may travel long distances to ignition sources and flashback. Vapors in confined area may explode in fire. Containers may explode in fire. Storage containers and parts of containers may rocket great distances, in many directions. If materials or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Notify local health and fire officials and pollution control agencies. From a secure, explosion-proof location, use water spray to cool exposed containers. If cooling streams are ineffective (venting sound increases in volume and pitch, tank discolors, or shows any signs of deforming), withdraw immediately to a secure position. If employees are expected to fight fires, they must be trained and equipped.


### Specific Hazards Arising from the Chemical

Excerpt from ERG Guide 129P [Flammable Liquids (Water-Miscible / Noxious)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. (ERG, 2016)

### Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

### NFPA 704



**HEALTH** 1 Exposure would cause irritation with only minor residual injury (e.g. [acetone](#), sodium bromate, potassium chloride)

**FIRE** 3 Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

**REACT** 1 Normally stable, but can become unstable at elevated temperatures and pressures (e.g. [propene](#))

SPEC.

HAZ.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing mist, gas or vapours. Avoid contacting with skin and eye. Use personal protective equipment. Wear chemical impermeable gloves. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

### Environmental precautions

Prevent further spillage or leakage if it is safe to do so. Do not let the chemical enter drains. Discharge into the environment must be avoided.

### Methods and materials for containment and cleaning up

Evacuate and restrict persons not wearing protective equipment from area of spill or leak until cleanup is complete. Remove all ignition sources. Establish forced ventilation to keep levels below explosive limit. Absorbent may be used to consolidate spills on land (such as sorbent polyurethane foams). Oil skimming equipment may be used for spills on water. Absorb liquids in vermiculite, dry sand, earth, or a similar non-organic materials and deposit in sealed containers. Keep this chemical out of a confined space, such as a sewer, because of the possibility of an explosion, unless the sewer is designed to prevent the build-up of explosive concentrations. It may be necessary to contain and dispose of this chemical as a hazardous waste. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Contact your Department of Environmental Protection or your regional office of the federal EPA for specific recommendations. If employees are required to clean-up spills, they must be properly trained and equipped.

## SECTION 7: Handling and storage

### Precautions for safe handling

Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

### Conditions for safe storage, including any incompatibilities

Prior to working with this chemical you should be trained on its proper handling and storage. Before entering a confined space where hexanol may be present, check to make sure that an explosive concentration does not exist. Store in an explosion-proof cool area. Protect for air and light for long-term storage. Where possible, automatically pump liquid from drums or other storage containers to process containers.

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### Occupational Exposure limit values

<b>Component</b>	Isobutyl acrylate			
<b>CAS No.</b>	106-63-8			
	<b>Limit value - Eight hours</b>		<b>Limit value - Short term</b>	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
<b>Finland</b>	2	11	10 (1)	53 (1)
	<b>Remarks</b>			
<b>Finland</b>	(1) 15 minutes average value			

#### Biological limit values

no data available

## Exposure controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

## Individual protection measures

### Eye/face protection

Wear tightly fitting safety goggles with side-shields conforming to EN 166(EU) or NIOSH (US).

### Skin protection

Wear fire/flammable resistant and impervious clothing. Handle with gloves. Gloves must be inspected prior to use. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

### Respiratory protection

If the exposure limits are exceeded, irritation or other symptoms are experienced, use a full-face respirator.

### Thermal hazards

no data available

---

## SECTION 9: Physical and chemical properties

### Information on basic physicochemical properties

Physical state	Isobutyl acrylate is a clear colorless liquid with an acrid odor. Flash point 86°F. Less dense than water. Vapors irritate eyes and respiratory system. May polymerize exothermically if heated or contaminated. If polymerization takes place inside a container, the container may rupture violently.
Colour	Clear liquid
Odour	Sharply odorous
Melting point/freezing point	-100°C(lit.)
Boiling point or initial boiling point and boiling range	132°C(lit.)
Flammability	no data available
Lower and upper explosion limit/flammability limit	Lower 1.9%, upper 8.0% (in air) (% by vol)
Flash point	32°C
Auto-ignition temperature	644° F (USCG, 1999)
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	0.822 CP at 70 deg F
Solubility	Slightly soluble (NTP, 1992)
Partition coefficient n-octanol/water	log Kow = 2.22
Vapour pressure	0.062mmHg at 25°C
Density and/or relative density	0.89g/mL at 25°C(lit.)
Relative vapour density	4.42 (Air = 1)
Particle characteristics	no data available

## SECTION 10: Stability and reactivity

### Reactivity

Highly flammable. Slightly soluble in water

### Chemical stability

no data available

### Possibility of hazardous reactions

Flammable when exposed to heat or flame ...ISOBUTYL ACRYLATE is an acrylate ester. Esters react with acids to liberate heat along with alcohols and acids. Strong oxidizing acids may cause a vigorous reaction that is sufficiently exothermic to ignite the reaction products. Heat is also generated by the interaction of esters with caustic solutions. Flammable hydrogen is generated by mixing esters with alkali metals and hydrides. Polymerizes readily in the presence of heat and light generating much heat; reacts with strong oxidants. REF [Handling Chemicals Safely, 1980. p. 235].

### Conditions to avoid

no data available

### Incompatible materials

Forms explosive mixture with air. Heat and contamination may cause polymerization. Reacts with strong acids, aliphatic amines, alkanolamines.

### Hazardous decomposition products

When heated to decomposition it emits acrid smoke and toxic fumes.

---

## SECTION 11: Toxicological information

### Acute toxicity

- Oral: LD50 Rat oral 7070 mg/kg
- Inhalation: no data available
- Dermal: no data available

### Skin corrosion/irritation

no data available

### Serious eye damage/irritation

no data available

### Respiratory or skin sensitization

no data available

### Germ cell mutagenicity

no data available

### Carcinogenicity

no data available

### **Reproductive toxicity**

no data available

### **STOT-single exposure**

no data available

### **STOT-repeated exposure**

no data available

### **Aspiration hazard**

no data available

---

## SECTION 12: Ecological information

### **Toxicity**

Toxicity to fish: LC50 Pimephales promelas (Fathead minnows, 29 days old, mean length 18.5 mm, mean weight 0.1 g) 2.09 mg/L/96 hr (95% confidence limit 1.92-2.28 mg/L); flow through, 24.0 deg C, hardness 45.3 mg/L (CaCO<sub>3</sub>), pH 7.61, dissolved oxygen 7.1 mg/L, alkalinity 49.8 mg/L (CaCO<sub>3</sub>) />97% purity

Toxicity to daphnia and other aquatic invertebrates: EC50 Daphnia magna 9.7 mg/L/48 hr, endpoint: immobilization

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

### **Persistence and degradability**

AEROBIC: By analogy to butyl acrylate, which biodegrades readily in the MITI test(1), biodegradation of isobutyl acrylate may be an important environmental fate process(SRC). Butyl acrylate, present at 100 mg/L, reached 61% of its theoretical BOD in 2 weeks using an activated sludge inoculum at 30 mg/L in the Japanese MITI test(1)..

### **Bioaccumulative potential**

An estimated BCF of 10 was calculated in fish for isobutyl acrylate(SRC), using a log Kow of 2.22(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

### **Mobility in soil**

The Koc of isobutyl acrylate is estimated as 66(SRC), using a water solubility of 2,000 mg/L(1) and a regression-derived equation(2). According to a classification scheme(3), this estimated Koc value suggests that isobutyl acrylate is expected to have high mobility in soil.

### **Other adverse effects**

no data available

---

## SECTION 13: Disposal considerations

### **Disposal methods**



## Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

## Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

---

## SECTION 14: Transport information

### UN Number

ADR/RID: UN2527 (For reference only, please check.)

IMDG: UN2527 (For reference only, please check.)

IATA: UN2527 (For reference only, please check.)

### UN Proper Shipping Name

ADR/RID: ISOBUTYL ACRYLATE, STABILIZED (For reference only, please check.)

IMDG: ISOBUTYL ACRYLATE, STABILIZED (For reference only, please check.)

IATA: ISOBUTYL ACRYLATE, STABILIZED (For reference only, please check.)

### Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

### Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

### Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

### Special precautions for user

no data available

### Transport in bulk according to IMO instruments

no data available

---

## SECTION 15: Regulatory information

## Safety, health and environmental regulations specific for the product in question

### European Inventory of Existing Commercial Chemical Substances (EINECS)

Listed.

### EC Inventory

Listed.

### United States Toxic Substances Control Act (TSCA) Inventory

Listed.

### China Catalog of Hazardous chemicals 2015

Listed.

### New Zealand Inventory of Chemicals (NZIoC)

Listed.

### PICCS

Listed.

### Vietnam National Chemical Inventory

Listed.

### IECSC

Listed.

### Korea Existing Chemicals List (KECL)

Listed.

---

## SECTION 16: Other information

### Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

### References

IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: [http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)

CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>  
Chemical Book

Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

**Disclaimer:**

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.