

Chemical Safety Data Sheet MSDS / SDS

N,N-Dimethyl-p-toluidine

Revision Date:2024-04-06 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : N,N-Dimethyl-p-toluidine
CBnumber : CB4196682
CAS : 99-97-8
EINECS Number : 202-805-4
Synonyms : N,N-Dimethyl-P-Toluidine,N,N,4-trimethylaniline

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification**GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Danger

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use ... for extinction.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to.....

Hazard statements

H227 Combustible liquid

H301 Toxic if swallowed

H311 Toxic in contact with skin

H315 Causes skin irritation

H319 Causes serious eye irritation

H331 Toxic if inhaled

H351 Suspected of causing cancer

H373 May cause damage to organs through prolonged or repeated exposure

H412 Harmful to aquatic life with long lasting effects

Disposal

WARNING.Cancer - <https://oehha.ca.gov/proposition-65/chemicals/nn-dimethyl-p-toluidine>

SECTION 3: Composition/information on ingredients

Substance

Product name	: N,N-Dimethyl-p-toluidine
Synonyms	: N,N-Dimethyl-P-Toluidine,N,N,4-trimethylaniline
CAS	: 99-97-8
EC number	: 202-805-4
MF	: C9H13N
MW	: 135.21

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g

in a 10% slurry) and consult a doctor as quickly as possible.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Nitrogen oxides (NO_x) Combustible.

Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

- SPEC.
 - HAZ.
-

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemisorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton?

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 30 min

Material tested: Butoject? (KCL 898)

Body Protection

protective clothing

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	yellow clear, liquid
Odour	unpleasant
Odour Threshold	No data available
pH	7,44 at 25 °C
Melting point/freezing point	Melting point: -15 °C - (ECHA) 211 °C - lit.

Initial boiling point and boiling range	90 - 92 °C at 13 hPa - lit.
Flash point	76 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1,2 %(V)
Vapour pressure	0,099 hPa at 20 °C
Vapour density	5,42
Relative density	No data available
Water solubility	0,65 g/l at 37 °C
Partition coefficient: n-octanol/water	log Pow: 1,73 at 35 °C - Bioaccumulation is not expected., (ECHA)
Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 14,4 mPa.s at 35 °C
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

Relative vapor density

5,42

SECTION 10: Stability and reactivity

Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents Nitric acid

acid halides Acid anhydrides acids

Conditions to avoid

Strong heating.

Incompatible materials

various plastics, Mild steel

Hazardous decomposition products

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Mouse - 139 mg/kg Remarks: (ECHA)

LC50 Inhalation - Rat - 4 h - 1,4 mg/l Remarks: (ECHA)

Symptoms: mucosal irritations, Cough, Shortness of breath LD50 Dermal - Rabbit - > 2.000 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 1 h (OECD Test Guideline 405)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation Result: negative

Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Oral - May cause damage to organs through prolonged or repeated exposure. - Reproductive organs

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

No data available

Toxicity

LD50 orally in Rabbit: 1650 mg/kg

SECTION 12: Ecological information

Toxicity

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) - 46 mg/l - 96 h Remarks: (ECOTOX Database)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

UN number

ADR/RID: 2810 IMDG: 2810 IATA: 2810

UN proper shipping name

ADR/RID: TOXIC LIQUID, ORGANIC, N.O.S. (N,N-dimethyl-p-toluidine) IMDG: TOXIC LIQUID, ORGANIC, N.O.S. (N,N-dimethyl-p-toluidine) IATA: Toxic liquid, organic, n.o.s. (N,N-dimethyl-p-toluidine)

Transport hazard class(es)

ADR/RID: 6.1 IMDG: 6.1 IATA: 6.1

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Not Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

EC Inventory:Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

[1] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

[2] ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

[3] ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

[5] ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

[6] Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

Depending on the degree of exposure, periodic medical examination is suggested. Specific treatment is necessary in case of poisoning with this substance; the appropriate means with instructions must be available. Insufficient data are available on the effect of this substance on human health, therefore utmost care must be taken.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.