

## Chemical Safety Data Sheet MSDS / SDS

**Tetramethyl orthosilicate**

Revision Date:2026-04-11 Revision Number:1

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product identifier**

Product name : Tetramethyl orthosilicate  
CBnumber : CB6177258  
CAS : 681-84-5  
EINECS Number : 211-656-4  
Synonyms : TMOS, Tetramethyl orthosilicate

**Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.  
Uses advised against : none

**Company Identification**

Company : Chemicalbook  
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing  
Telephone : 010-86108875

**SECTION 2: Hazards identification****GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Danger

**Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

**Hazard statements**

H330 Fatal if inhaled

H318 Causes serious eye damage

H315 Causes skin irritation

## SECTION 3: Composition/information on ingredients

### Substance

Product name	: Tetramethyl orthosilicate
Synonyms	: TMOS, Tetramethyl orthosilicate
CAS	: 681-84-5
EC number	: 211-656-4
MF	: C <sub>4</sub> H <sub>12</sub> O <sub>4</sub> Si
MW	: 152.22

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

### 4.4 Notes to physician

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides silicon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.


Development of hazardous combustion gases or vapours possible in the event of fire.

## 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

## NFPA 704



**HEALTH 3** Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

**FIRE 3** Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, [acetone](#))

**REACT 1** Normally stable, but can become unstable at elevated temperatures and pressures (e.g. [propene](#))

**SPEC.**  
**HAZ.**

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemizorb®). Dispose of properly. Clean up affected area.

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

['Component', 'CAS-No.', 'Value', 'Control parameters', 'Basis']	['Silicic acid tetramethyl ester', '681-84-5', 'TWA', '1 ppm', 'USA. ACGIH Threshold Limit Values (TLV)']	['", ', 'TWA', '1 ppm6 mg/m3', 'USA. NIOSH Recommended Exposure Limits']
--	---	--

PEL 1 ppm6 California permissible exposure mg/m3 limits for chemical contaminants (Title 8, Article 107)

### 8.2 Exposure controls

#### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

#### Personal protective equipment

##### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-

approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-

approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 240 min

Material tested: KCL 720 Camapren®

#### Body Protection

Flame retardant antistatic protective clothing.

#### Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards:

DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

#### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### Information on basic physicochemical properties

a) Physical state	liquid
b) Color	colorless, to, yellow
c) Odor	aromatic
d) Melting point/freezing point	Melting point/ range: 3 °C at 1,013 hPa - OECD Test Guideline 102
e) Initial boiling point and boiling range	121 - 122 °C at 1,013 hPa
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	Upper explosion limit: 23.8 %(V) Lower explosion limit: 0.88 %(V) - DIN 51649
h) Flash point	26 °C - closed cup
i) Autoignition temperature	245 °C at 1,013 hPa - DIN 51794

j) Decomposition temperature	No data available
k) pH	No data available
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 0.7 mPa.s at 20 °C
m) Water solubility	hydrolyzes
n) Partition coefficient n-octanol/water	No data available
o) Vapor pressure	13 hPa at 20 °C - OECD Test Guideline 104 18 hPa at 25 °C - OECD Test Guideline 104
p) Density	1.03 g/cm <sup>3</sup> at 20 °C
Relative density	1.023 g/mL at 25 °C(lit.)
q) Relative vapor density	5.25 (vs air)
r) Particle characteristics	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none

## 9.2 Other safety information

### Relative vapor density

5.26 - (Air = 1.0)

## SECTION 10: Stability and reactivity

### 10.1 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.2 Possibility of hazardous reactions

Exothermic reaction with:

Alkali metals

Alkaline earth metals

Oxidizing agents acids

Water

Possible decomposition products in case of hydrolysis are:

Methanol

### 10.3 Conditions to avoid

Heating.

### 10.4 Incompatible materials

No data available

### 10.5 Hazardous decomposition products

In the event of fire: see section 5

## SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

### Acute toxicity

LD50 Oral - Rat - male and female - > 2,500 mg/kg (OECD Test Guideline 423)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

LC50 Inhalation - Rat - male - 4 h - 0.39 mg/l - vapor (OECD Test Guideline 403)

Symptoms: Possible damages: mucosal irritations, Lung edema

LD50 Dermal - Rabbit - 17,544 mg/kg

Remarks: (RTECS)

### Skin corrosion/irritation

Skin - Rat

Result: Irritating to skin. - 4 h (OECD Test Guideline 404)

### Serious eye damage/eye irritation

Remarks: Risk of blindness! (ECHA)

### Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative (OECD Test Guideline 406)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

### Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vivo micronucleus test

Species: Rat

Cell type: Bone marrow

Application Route: inhalation (vapor)

Method: OECD Test Guideline 474

Result: negative

### Carcinogenicity

Classified based on available data. For more details, see section 2

### Reproductive toxicity

Classified based on available data. For more details, see section 2

### Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

### Specific target organ toxicity - repeated exposure

Classified based on available data. For more details, see section 2

### Aspiration hazard

Classified based on available data. For more details, see section 2

## 11.2 Additional Information

Blindness, Effects due to ingestion may include: Nausea, Vomiting, Gastrointestinal disturbance, Dizziness, Difficulty in breathing, Weakness, Drowsiness, Unconsciousness

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After absorption of large quantities:

Damage to:

Liver

Kidney

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish semi-static test LC50 - *Danio rerio* (zebra fish) - > 1,000 mg/l - 96 h (OECD Test Guideline 203)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

Toxicity to daphnia flow-through test EC50 - *Daphnia magna* (Water flea) - > 500 mg/l - and other aquatic 48 h invertebrates (OECD Test Guideline 202)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

Toxicity to algae static test ErC50 - *Pseudokirchneriella subcapitata* (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

Toxicity to bacteria static test EC50 - activated sludge - > 100 mg/l - 3 h (OECD Test Guideline 209)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 98 % - Readily biodegradable.

(Regulation (EC) No. 440/2008, Annex, C.4-A)

Remarks: The value is given in analogy to the following substances: tetraethyl silicate

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

Possible decomposition products in case of hydrolysis are:

Methanol

Discharge into the environment must be avoided.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR/RID: 2606

IMDG: 2606

IATA-DGR: 2606

### 14.2 UN proper shipping name

ADR/RID: METHYL ORTHOSILICATE

IMDG: METHYL ORTHOSILICATE

IATA-DGR: Methyl orthosilicate

Passenger Aircraft: Not permitted for transport

Cargo Aircraft: Not permitted for transport

### 14.3 Transport hazard class(es)

ADR/RID: 6.1 (3)

IMDG: 6.1 (3)

IATA-DGR: 6.1 (3)

### 14.4 Packaging group

ADR/RID: I

IMDG: I

IATA-DGR: -

### 14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA-DGR: no

### 14.6 Special precautions for user

Based on chemical properties, choose appropriate tools and conditions of transport.

Transporting tools shall be equipped with appropriate and sufficient firefighting equipment and emergency leaking installations. If transporting by road, please go along the specified route.

### 14.7 Incompatible materials

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Other regulations

Please pay attention on the waste treatment should also comply with local regulations requirement.

---

## SECTION 16: Other information

### Abbreviations and acronyms

CAS: Chemical Abstracts Service

TWA: Time-Weighted Average

STEL: Short-Term Exposure Limit

LD50: Lethal Dose 50%

LC50: Lethal Concentration 50%

EC50: Effective Concentration 50%

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

DOT: US Department of Transportation

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

#### Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.