

Chemical Safety Data Sheet MSDS / SDS

Vinylene carbonate

Revision Date:2026-03-21 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Vinylene carbonate
CBnumber : CB9119200
CAS : 872-36-6
EINECS Number : 212-825-5
Synonyms : 1,3-DIOXOL-2-ONE;vinyl carbonate

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P314 Get medical advice/attention if you feel unwell.

Hazard statements

H302 Harmful if swallowed
H311 Toxic in contact with skin
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H318 Causes serious eye damage
H373 May cause damage to organs through prolonged or repeated exposure

SECTION 3: Composition/information on ingredients

Substance

Product name	: Vinylene carbonate
Synonyms	: 1,3-DIOXOL-2-ONE; vinyl carbonate
CAS	: 872-36-6
EC number	: 212-825-5
MF	: C ₃ H ₂ O ₃
MW	: 86.05

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

4.4 Notes to physician

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.


Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

REACT 1 Normally stable, but can become unstable at elevated temperatures and pressures (e.g. [propene](#))

SPEC.
HAZ.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stability

Recommended storage temperature 2 - 8 °C

Storage class

Storage class (TRGS 510): 6.1C: Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

['Component', 'CAS-No.', 'Value', 'Control parameters', 'Basis']	['butyl hydroxytoluene (BHT)', '128-37-0', 'TWA', '2 mg/m3', 'USA ACGIH Threshold Limit Values (TLV)']	['', 'Remarks', 'Not classifiable as a human carcinogen', 'None, None']	['', '', 'TWA', '10 mg/m3', 'USA NIOSH Recommended Exposure Limits']	['', '', 'PEL', '10 mg/m3', 'California permissible exposure limits for chemical contaminants (Title 8, Article 107)']
--	--	---	--	--

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly

fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 51 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

a) Physical state	liquid
b) Color	light yellow
c) Odor	No data available
d) Melting point/freezing point	Melting point/range: 19 - 22 °C
e) Initial boiling point and boiling range	162 °C
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	No data available
h) Flash point	73 °C - closed cup
i) Autoignition temperature	355 °C at 1,007.3 - 1,013 hPa

j) Decomposition temperature	No data available
k) pH	No data available
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m) Water solubility	515 g/l at 20.2 °C - OECD Test Guideline 105- soluble
n) Partition coefficient n-octanol/water	log Pow: -0.36 at 20 °C
o) Vapor pressure	3.35hPa at 25°C
p) Density	1.355 g/mL at 25 °C
Relative density	1.360 g/mL at 20 °C
q) Relative vapor density	No data available
r) Particle characteristics	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none
Solubility	11.5 g/100 mL

9.2 Other safety information

Surface tension

73.4 mN/m at 19.9 °C

SECTION 10: Stability and reactivity

10.1 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Contains the following stabilizer(s): butyl hydroxytoluene (BHT) (<2 %)

10.2 Possibility of hazardous reactions

No data available

10.3 Conditions to avoid

Strong heating.

10.4 Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents

10.5 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 500 mg/kg (Calculation method)

LD50 Oral - Rat - male and female - > 300 - < 500 mg/kg (Directive 67/548/EEC, Annex V, B.1.)

Inhalation: No data available

Acute toxicity estimate Dermal - 300 mg/kg (Calculation method)

LD50 Dermal - Rat - male and female - > 200 - < 2,000 mg/kg (Directive 67/548/EEC, Annex V, B.3.)

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Risk of serious damage to eyes. - 24 h (OECD Test Guideline 405)

Respiratory or skin sensitization

- Mouse

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Test Type: Ames test

Test system: E. coli

Metabolic activation: with and without metabolic activation

Result: negative

Species: Mouse

Application Route: Oral

Method: Micronucleus test

Result: negative

Carcinogenicity

Classified based on available data. For more details, see section 2

Reproductive toxicity

Classified based on available data. For more details, see section 2

Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

Specific target organ toxicity - repeated exposure

Ingestion - May cause damage to organs through prolonged or repeated exposure.

- Liver, Stomach

Aspiration hazard

Classified based on available data. For more details, see section 2

11.2 Additional Information

RTECS: FG3325000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish mortality LC50 - Cyprinus carpio (Carp) - 2.4 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - 4.9 mg/l - 48 h and other aquatic (OECD Test Guideline 202)

invertebrates

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata (green algae) - 3.2 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria EC50 - Sludge Treatment - 100 mg/l - 3 h

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 22 % - Not rapidly biodegradable (OECD Test Guideline 301D)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2810

IMDG: 2810

IATA-DGR: 2810

14.2 UN proper shipping name

ADR/RID: TOXIC LIQUID, ORGANIC, N.O.S. (1,3-Dioxol-2-one)

IMDG: TOXIC LIQUID, ORGANIC, N.O.S. (1,3-Dioxol-2-one)

IATA-DGR: Toxic liquid, organic, n.o.s. (1,3-Dioxol-2-one)

14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA-DGR: 6.1

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA-DGR: III

14.5 Environmental hazards

ADR/RID: yes

IMDG Marine pollutant: yes

IATA-DGR: no

14.6 Special precautions for user

Based on chemical properties, choose appropriate tools and conditions of transport.

Transporting tools shall be equipped with appropriate and sufficient firefighting equipment and emergency leaking installations. If transporting by road, please go along the specified route.

14.7 Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Other regulations

Please pay attention on the waste treatment should also comply with local regulations requirement.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

TWA: Time-Weighted Average

STEL: Short-Term Exposure Limit

LD50: Lethal Dose 50%

LC50: Lethal Concentration 50%

EC50: Effective Concentration 50%

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

DOT: US Department of Transportation

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.